

GFRP DIS Boxes & Trackside Connection Boxes

A comprehensive range of electrical connection boxes for points heating, trackside power and signalling applications.

Delivered pre-assembled with all terminals, links and a range of mounting options

All enclosures incorporate a Padlock Hasp compatible with NR 221/222 Padlocks



For more information visit
www.ilecsysrail.co.uk
Or call us: 01442 828387



- **IP66 Ingress Protection**
- **IK10 Impact Resistance**
- **High impact, lightweight composite enclosure**
- **Easy to Install - Many mounting options including pedestal, Rod Roller Bracket or Rear Surface Mount. The assembly may also be mounted directly onto a Trough Mounted Support Plate - PADs No: 0086/011920**
- **No Coatings - No Maintenance. Typ. Dielectric strength in excess of 5kV**
- **Suitable for all signalling disconnect requirements including: AWS, TPWS, Axle Counters and Point Machines applications. In addition, enclosures can be configured for all common E&P applications including:**
 - Modular Signalling Power Connections
 - 8 and 16 Way Strip Heater
 - Clamp Lock HOT/COLD Probe Connections
 - Signalling Power Distribution
- **Supplied complete with Heat Shrink/Compression Glands, Uni-Strut Cable Clamp Bar and Betaduct Trunking**
- **Sizes available from 300mm x 250mm to 1000mm x 800mm**
- **PAD's approved unpopulated enclosures available for other applications**

More information can be found online at www.ilecsysrail.co.uk

Unit 4 • Tring Industrial Estate • Tring • Herts •
HP23 4JX
t: 01442 828387
f: 01442 828399
e-mail: enquiry@ilecsysrail.co.uk

